

Catalogue 2015 - ref: 2015-1

Glass Fibre Cover Water



OUTSIDE TEMP. UP TO 600°C

REF	DESIGNATION	Nominal		Diamètre en mm			Pression en bar		Aspiration en bar	Rayon min. de courbure en mm	Poids en g/m	L mini m
		mm	pouce	Intérieur	Renfort	Extérieur	Service	Eclat.				
	GLASS FIBRE COVER WATER 10	10	3/8"	10,0		20,0	7	21		100	0,311	61
	GLASS FIBRE COVER WATER 12	12	1/2"	12,7		22,0	7	21		130	0,358	61
	GLASS FIBRE COVER WATER 16	16	5/8"	16,0		25,0	7	21		160	0,438	61
	GLASS FIBRE COVER WATER 19	19	3/4"	19,0		29,0	7	21		190	0,515	61
	GLASS FIBRE COVER WATER 25	25	1"	25,4		35,0	7	21		254	0,637	61
	GLASS FIBRE COVER WATER 12	32	1 1/4"	32,0		41,5	7	21		320	0,846	61
	GLASS FIBRE COVER WATER 38	38	1 1/2"	38,0		50,0	7	21		380	0,969	61
	GLASS FIBRE COVER WATER 44	44	1 3/4"	44,5		55,0	7	21		445	1,221	61
	GLASS FIBRE COVER WATER 50	50	2"	50,8		63,0	7	21		508	1,404	61
	GLASS FIBRE COVER WATER 63	63	2 1/2"	63,5		76,0	7	21		635	2,038	61
	GLASS FIBRE COVER WATER 76	76	3"	76,2		89,0	7	21		762	2,536	61
	GLASS FIBRE COVER WATER 101	101	4"	101,6		115,0	7	21		1016	3,313	61
	GLASS FIBRE COVER WATER 127	127	5"	127,0		145,0	7	21		1270	5,158	61

Données à titre indicatif, sous réserve de modifications sans préavis du fabricant



STRUCTURE:

Tube intérieur: Caoutchouc naturel et synthétique noir.

Renfort: Insertion textile haute tenacité.

Tube extérieur: Caoutchouc synthétique noir, résistant à la chaleur jusqu'à 600°C et aux agents atmosphériques revêtu de fibre de verre.

APPLICATIONS:

Pour le transfert des eaux de refroidissement dans les aciéries et les fonderies.

TEMPERATURE D'EMPLOI:

de - 25° C à + 75° C

NORMES:

ISO 1307

OPTIONS:

Sur demande: Température extérieure jusqu'à 1200°C.



STRUCTURE:

Tube: Black natural and synthetic rubber.

Reinforcement : High tensile synthetic textile.

Cover: Black, heat (up to 600°C), weather resistant synthetic rubber a,d glass fiber.

APPLICATIONS:

For cooling water transfer in steel mills and foundries.

TEMPERATURE:

de - 13° F à + 158° F

NORMS:

ISO 1307

OPTIONS:

Upon request: Outside temperature up to 1200°C.