

Catalogue 2015 - ref: 2015-1

## Beer & Wine Delivery



REF	DESIGNATION	Nominal		Diamètre en mm			Pression en bar		Aspiration en bar	Rayon min. de courbure en mm	Poids en kg/m	L mini m
		mm	pouce	Intérieur	Renfort	Extérieur	Service	Eclat.				
<b>6 BAR</b>												
	BEER & WINE DELIVERY 19	19	3/4"	19,0		28,5	6	18		190	0,472	40-46-61
	BEER & WINE DELIVERY 25	25	1"	25,4		35,0	6	18		254	0,600	40-46-61
	BEER & WINE DELIVERY 32	32	1 1/4"	32,0		43,0	6	18		320	0,887	40-46-61
	BEER & WINE DELIVERY 38	38	1 1/2"	38,0		49,0	6	18		380	0,990	40-46-61
	BEER & WINE DELIVERY 44	44	1 3/4"	44,5		55,5	6	18		445	1,140	40-46-61
	BEER & WINE DELIVERY 50	50	2"	50,8		62,0	6	18		5103	1,315	40-46-61
	BEER & WINE DELIVERY 63	63	2 1/2"	63,5		75,0	6	18		635	1,665	40-46-61
	BEER & WINE DELIVERY 76	76	3"	76,2		89,0	6	18		762	2,145	40-46-61
	BEER & WINE DELIVERY 101	101	4"	101,6		115,0	6	18		1016	2,930	40-46-61
<b>10 BAR</b>												
	BEER & WINE DELIVERY 19	19	3/4"	19,0		30,0	10	30		190	0,556	40-46-61
	BEER & WINE DELIVERY 25	25	1"	25,4		37,0	10	30		254	0,719	40-46-61
	BEER & WINE DELIVERY 32	32	1 1/4"	32,0		44,0	10	30		320	0,945	40-46-61
	BEER & WINE DELIVERY 38	38	1 1/2"	38,0		51,0	10	30		380	1,186	40-46-61
	BEER & WINE DELIVERY 44	44	1 3/4"	44,5		57,5	10	30		445	1,360	40-46-61
	BEER & WINE DELIVERY 50	50	2"	50,8		65,0	10	30		510	1,657	40-46-61
	BEER & WINE DELIVERY 63	63	2 1/2"	63,5		77,5	10	30		635	2,078	40-46-61
	BEER & WINE DELIVERY 76	76	3"	76,2		92,0	10	30		762	2,680	40-46-61
	BEER & WINE DELIVERY 101	101	4"	101,6		117,5	10	30		1016	3,544	40-46-61

Données à titre indicatif, sous réserve de modifications sans préavis du fabricant



### STRUCTURE:

**Tube intérieur:** Caoutchouc EPDM couleur blanche, non toxique, anti odeur et ne transmettant pas de gout.

**Renfort:** Insertion textile haute tenacité.

**Tube extérieur:** Caoutchouc synthétique spécial, résistant à l'abrasion, à l'ozone et aux agents atmosphériques.

### APPLICATIONS:

Pour le refoulement de boissons telles que le vin, les liqueurs, la bière, l'eau minérales, jus de fruits, etc...

### TEMPERATURE D'EMPLOI:

de - 40° C à + 120° C

### NORMES:

ISO 1307 MEETS FDA AND EUROPEAN REQUIREMENTS

### SANIFICATION:

130° C max. pendant 15 min. avec vapeur 60° C max. pendant 15 min. avec soude caustique (5%).

### COULEURS:



### STRUCTURE:

**Tube:** White colour, non toxic, taste and odour free, EPDM rubber.

**Reinforcement :** High tensile synthetic textile.

**Cover:** Weather, ozone and abrasion resistant, special synthetic rubber.

### APPLICATIONS:

For delivery of beverages such as wine, liqueur, beer, fruit juice, mineral water, etc...

### TEMPERATURE:

de - 40° F à + 248° F

### NORMS:

ISO 1307 MEETS FDA AND EUROPEAN REQUIREMENTS

### SANIFICATION:

Max. 130° C for 15 min. with steam, max. 60° C for 15 min. with caustic soda (5%).