

Catalogue 2015 - ref: 2015-1

## Radiator



| REF | DESIGNATION  | Nominal |         | Diamètre en mm |         |           | Pression en bar |        | Aspiration en bar | Rayon min. de courbure en mm | Poids en g/m | L mini m   |
|-----|--------------|---------|---------|----------------|---------|-----------|-----------------|--------|-------------------|------------------------------|--------------|------------|
|     |              | mm      | pouce   | Intérieur      | Renfort | Extérieur | Service         | Eclat. |                   |                              |              |            |
|     | RADIATOR 12  | 12      | 1/2"    | 12,7           |         | 19,0      | 4               | 12     |                   |                              | 0,215        | 1-40-46-61 |
|     | RADIATOR 16  | 16      | 5/8"    | 16,0           |         | 22,0      | 4               | 12     |                   |                              | 0,260        | 1-40-46-61 |
|     | RADIATOR 18  | 18      | -       | 18,0           |         | 24,0      | 4               | 12     |                   |                              | 0,288        | 1-40-46-61 |
|     | RADIATOR 19  | 19      | 3/4"    | 19,0           |         | 25,0      | 4               | 12     |                   |                              | 0,302        | 1-40-46-61 |
|     | RADIATOR 20  | 20      | -       | 20,0           |         | 26,0      | 4               | 12     |                   |                              | 0,315        | 1-40-46-61 |
|     | RADIATOR 22  | 22      | 7/8"    | 22,0           |         | 28,0      | 4               | 12     |                   |                              | 0,343        | 1-40-46-61 |
|     | RADIATOR 25  | 25      | 1"      | 25,4           |         | 32,0      | 4               | 12     |                   |                              | 0,432        | 1-40-46-61 |
|     | RADIATOR 28  | 28      | 1 1/8"  | 28,0           |         | 34,5      | 4               | 12     |                   |                              | 0,472        | 1-40-46-61 |
|     | RADIATOR 30  | 30      | 1 3/16" | 30,0           |         | 38,0      | 4               | 12     |                   |                              | 0,600        | 1-40-46-61 |
|     | RADIATOR 32  | 32      | 1 1/4"  | 32,0           |         | 40,0      | 4               | 12     |                   |                              | 0,636        | 1-40-46-61 |
|     | RADIATOR 35  | 35      | 1 3/8"  | 35,0           |         | 43,0      | 4               | 12     |                   |                              | 0,690        | 1-40-46-61 |
|     | RADIATOR 38  | 38      | 1 1/2"  | 38,0           |         | 47,0      | 4               | 12     |                   |                              | 0,845        | 1-40-46-61 |
|     | RADIATOR 40  | 40      | 1 9/16" | 40,0           |         | 49,0      | 4               | 12     |                   |                              | 0,886        | 1-40-46-61 |
|     | RADIATOR 42  | 42      | 1 5/8"  | 42,0           |         | 51,0      | 4               | 12     |                   |                              | 0,926        | 1-40-46-61 |
|     | RADIATOR 44  | 44      | 1 3/4"  | 44,5           |         | 54,0      | 4               | 12     |                   |                              | 1,050        | 1-40-46-61 |
|     | RADIATOR 48  | 48      | 1 7/8"  | 48,0           |         | 57,5      | 4               | 12     |                   |                              | 1,122        | 1-40-46-61 |
|     | RADIATOR 50  | 50      | 2"      | 50,9           |         | 60,0      | 4               | 12     |                   |                              | 1,182        | 1-40-46-61 |
|     | RADIATOR 55  | 55      | 2 3/16" | 55,0           |         | 65,0      | 4               | 12     |                   |                              | 1,360        | 1-40-46-61 |
|     | RADIATOR 60  | 60      | 2 3/8"  | 60,0           |         | 70,0      | 4               | 12     |                   |                              | 1,470        | 1-40-46-61 |
|     | RADIATOR 63  | 63      | 2 1/2"  | 63,5           |         | 73,5      | 4               | 12     |                   |                              | 1,490        | 1-40-46-61 |
|     | RADIATOR 70  | 70      | 2 3/4"  | 70,0           |         | 80,0      | 4               | 12     |                   |                              | 1,630        | 1-40-46-61 |
|     | RADIATOR 76  | 76      | 3"      | 76,2           |         | 86,0      | 4               | 12     |                   |                              | 1,765        | 1-40-46-61 |
|     | RADIATOR 80  | 80      | 3 1/8"  | 80,0           |         | 90,0      | 4               | 12     |                   |                              | 1,845        | 1-40-46-61 |
|     | RADIATOR 90  | 90      | 3 1/2"  | 90,0           |         | 100,0     | 4               | 12     |                   |                              | 2,065        | 1-40-46-61 |
|     | RADIATOR 101 | 101     | 4"      | 101,6          |         | 111,5     | 4               | 12     |                   |                              | 2,300        | 1-40-46-61 |

Données à titre indicatif, sous réserve de modifications sans préavis du fabricant



### STRUCTURE:

**Tube intérieur:** Caoutchouc EPDM résistant à la chaleur et antigel.

**Renfort :** Insertion de textile haute tenacité.

**Tube extérieur:** Caoutchouc EPDM, résistant à la chaleur, au vieillissement et aux agents atmosphériques.

### APPLICATIONS:

Pour passage d'eau chaude et antigel dans les systèmes de refroidissement des moteurs thermiques secteur automobiles et industrie.

### TEMPERATURE D'EMPLOI:

de - 40° C à + 125° C

### NORMES:

DIN 73411 - TS 548 - ISO 1307 Upon Request : DIN 5510-2



### STRUCTURE:

**Tube:** Heat and anti-freeze liquids EPDM rubber.

**Reinforcement :** high tensile synthetic textile.

**Cover:** Heat, ageing and weather resistant rubber.

### APPLICATIONS:

For conveying hot water mixed with anti-freeze liquids in cooling systems, automotive and stationary engines.

### TEMPERATURE:

de - 40° F à + 257° F

### NORMS:

DIN 73411 - TS 548 - ISO 1307 Upon Request : DIN 5510-2